

Adheres to Metal, Rubber,
Glass and most Plastics
Effective at Temperatures
From -110°F to +1050°F

Non-Corrosive, Non-Conductive,
and Waterproof

Moly D Film Lubricant and Coating is a superior, long-lasting dry lubricant that adheres to almost all materials. Withstands high temperatures and pressures. Repels dust and dirt and is resistant to water, alkalies and most acids. Greatly increases operating efficiency and reduces maintenance costs. Prevents corrosion, seizing, wear, galling, binding, sticking, chattering, squeaking and scraping.

Designed for high pressure, load-bearing applications. Excellent for anti-friction and anti-seize where a dust and dirt resistant dry lubricant is desirable. Withstands temperature ranges from -110°F to +1050°F. Resists pressures up to 100,000 psi. Contains pure Molybdenum Disulfide micro-particles which burnish themselves into metal surfaces and provide a bonded dry lubricating film.

INDUSTRIAL APPLICATIONS:

Oil Drilling Equipment, Foundries, Automotive Plants, Vehicle Maintenance, Sewing Trades, Paper and Corrugated Converting, Chemical Plants, Woodworking, Marine, Agricultural & Military Equipment, Road Equipment, Aircraft Maintenance, Steel Mills and Mining Operations.

USES:

May be applied wherever petroleum or synthetic lubricants are not suitable (except oxygen systems). Use on gears, bellcranks, slides, chutes, bearing surfaces, press fits, chains, conveyors, cylinder packings, shafts, valve stems, vulcanized rubber molds. High load carrying qualities assure lubrication under extreme pressures. Lubricates construction and other heavy equipment. Eliminates chattering and scraping. Resists water and dirt.

DIRECTIONS:

Shake can vigorously before application. Surface must be clean and dry prior to application. Hold can 8 to 10 inches from surface and spray in a sweeping motion to insure a thin uniform coating. Allow to set approximately 3 to 5 minutes before applying second coat. **IMPORTANT:** To prevent clogging, after each use, invert can and spray a few short bursts to clear valve.

WEICHEM, INC.

5734 Susitna Dr. Harahan, LA 70123
504.733.1152 · 1.800.426.0512
FAX 504.733.2218 · www.wechem.com



Engineered Chemistries
SUPERIOR SOLUTIONS

MOLY D™

FILM LUBRICANT & COATING

Non-Chlorinated
Anti-Friction
Anti-Seize
Non-Corrosive
Waterproof

DANGER:
EXTREMELY FLAMMABLE.
HARMFUL OR FATAL IF SWALLOWED.
EYE AND SKIN IRRITANT.
CONTENTS UNDER PRESSURE.
SEE OTHER CAUTIONS ON SIDE PANEL.

NET WT. 12 OZ/340 g

REV 3/15

MOLY-D



DANGER: Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer. May damage fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 49°C/120°F. Dispose of contents/container in accordance with local/regional/national/international regulations.

IF SWALLOWED: Immediately call a poison center/doctor. Do NOT induce vomiting.

IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

IF EXPOSED OR CONCERNED: Get medical advice/attention.

CONTAINS: Acetone (67-64-1), Butane (106-97-8), Propane (74-98-6), Aliphatic Petroleum Solvent (64742-89-8), Magnesium Silicate (14807-96-6), n-Heptane (142-82-5), Toluene (108-88-3), Cyclohexane (110-82-7), Methyl Ethyl Ketoxime (96-29-7) and n-Hexane (110-54-3).

Caution: Use with adequate ventilation. Intentional misuse by concentrating and inhaling the product can be harmful or fatal. **KEEP OUT OF REACH OF CHILDREN.**

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

See Safety Data Sheet for complete safety information. **24 HOUR MEDICAL EMERGENCY: 1-866-836-8855. CONTAINS NO OZONE DEPLETING CHEMICALS!**