

**No Chlorinated Solvents
(No 1,1,1-Trichloroethane)**

PROTECTO FLEX is a long-term, flexible, non-tacky dust-resistant coating that will not crack, peel, flake or chip over a wide temperature range (-40°F to +175°F). Adheres to most clean metal surfaces.

PROTECTO FLEX provides a translucent coating which allows identification codes underneath to be easily read. **PROTECTO FLEX** can be flushed off easily with mineral spirits whereas other coatings are difficult to remove and usually require special solvents.

Please do not store in temperatures below 50°F.

This product has an expected shelf life of 2 years from the date of manufacture as indicated by the code on the bottom of the can.

USE ON:

Large molds, offshore drilling parts, outdoor airport ground handling equipment, castings, metal parts in ground or ocean transit, seasonal equipment in storage and any metal part needing to be temporarily sealed against corrosion.

DIRECTIONS: SHAKE THIS PRODUCT WELL BEFORE AND DURING USE. Make sure surface is clean and dry. Spray a thin uniform film. Allow approximately 5 minutes to set up. For more severe storage conditions, a second coating can be applied within a few minutes. Complete setting of protective coating takes approximately two hours after spraying.



Engineered Chemistries
SUPERIOR SOLUTIONS

Protecto Flex

LONG TERM METAL PARTS PROTECTOR

NON-CHLORINATED CORROSION PREVENTATIVE

FLEXIBLE DUST RETARDANT COATING

SEE-THROUGH FILM ALLOWS PARTS TO BE IDENTIFIED

EASILY APPLIED AND REMOVED

**DANGER:
EXTREMELY FLAMMABLE
HARMFUL OR FATAL IF SWALLOWED
CONTACT WITH EYES AND SKIN MAY
CAUSE IRRITATION.
CONTENTS UNDER PRESSURE
SEE OTHER CAUTIONS ON SIDE PANEL**

NET WT. 14 OZ. / 396 g



DANGER: Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container. Do not pierce or burn, even after use. Wash thoroughly after handling. Wear protective gloves. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 49°C/120°F. Dispose of contents/container in accordance with local/regional/national/international regulations.

IF SWALLOWED: Immediately call a poison center/doctor. Do NOT induce vomiting.

IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

IF EXPOSED OR CONCERNED: Get medical advice/attention.

IF IN EYES: Rinse with water. Get medical attention if irritation develops and persists.

IF INHALED: If symptoms develop move victim to fresh air. Get medical attention if symptoms persist.

CONTAINS: Butane (106-97-8), Mineral Spirits (8052-41-3), Propane (74-98-6) and Synthetic Isoparaffinic Hydrocarbon (64741-66-8).

Caution: Use with adequate ventilation. Intentional misuse by concentrating and inhaling the product can be harmful or fatal.

KEEP OUT OF REACH OF CHILDREN.

See Safety Data Sheet for complete safety information. 24 HOUR MEDICAL EMERGENCY: 1-866-836-8855. CONTAINS NO OZONE DEPLETING CHEMICALS!



WECHEM, INC.

5734 Susitna Dr. Harahan, LA 70123
504.733.1152 · 1.800.426.0512
FAX 504.733.2218 · www.wechem.com