

## Wheel Luster

MSDS Number: V69E

Revision Date: 6/9/2015

Page 1 of 6

### 1 PRODUCT AND COMPANY IDENTIFICATION

#### Manufacturer

Wechem, Inc  
5734 Susitna Dr  
Harahan, LA 70123

**Contact:** Ligia M. Hernandez  
**Phone:** 504-733-1152  
**Fax:** 504-733-2218  
**Web:** www.wechem.com

**Product Name:** Wheel Luster  
**Revision Date:** 6/9/2015  
**MSDS Number:** V69E  
**Product Code:** V69  
**Product Use:** Non-Acid Wheel and Tire Cleaner & Brake Dust Solvent

Emergency Telephone Number:  
INFOTRAC  
1-800-535-5053

### 2 HAZARDS IDENTIFICATION

**Route of Entry:** Skin absorption, ingestion, eyes, inhalation  
**Target Organs:** NA  
**Inhalation:** Inhalation of generated mist can cause nasal and respiratory irritation or damage to respiratory tract.  
**Skin Contact:** Corrosive. Causes severe irritation or skin burns.  
**Eye Contact:** Causes serious eye damage.  
**Ingestion:** Harmful or fatal if swallowed.

PERSONAL PROTECTION INDEX									
A									
B		+							
C		+		+					
D		+		+					
E		+		+					
F		+		+		+			
G		+		+					
H		+		+		+			
I		+		+					
J		+		+		+			
K		+		+		+			
X	Consult your supervisor or S.O.P. for "SPECIAL" handling directions								
A		n		o		p		q	
<small>Safety Glasses</small>	<small>Safety Goggles</small>	<small>Face Shield &amp; Eye Protection</small>	<small>Gloves</small>	<small>Boots</small>	<small>Synthetic Apron</small>	<small>Full Suit</small>	<small>Additional Information</small>		
t		u		w		y		z	
<small>Dust Respirator</small>	<small>Vapor Respirator</small>	<small>Dust &amp; Vapor Respirator</small>	<small>Full Face Respirator</small>	<small>Airline Hood or Mask</small>					

## Wheel Luster

MSDS Number: V69E

Revision Date: 6/9/2015

Page 2 of 6

GHS Signal Word:  
DANGER

GHS Hazard Pictograms:



GHS Classifications:  
Health, Acute toxicity, 4 Oral  
Health, Skin corrosion/irritation, 1 B  
Health, Specific target organ toxicity - Single exposure, 3

GHS Phrases:  
H302 - Harmful if swallowed  
H314 - Causes severe skin burns and eye damage  
H335 - May cause respiratory irritation

GHS Precautionary Statements:  
P260 - Do not breathe dust/fume/gas/mist/vapors/spray.  
P280 - Wear protective gloves/protective clothing/eye protection/face protection.  
P301+310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.  
P301+330+331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
P303+361+353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P333+313 - If skin irritation or a rash occurs: Get immediate medical advice/attention.  
P363 - Wash contaminated clothing before reuse.  
P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
P304+312 - IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.  
P305+351+338 - IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.  
P315 - Get immediate medical advice/attention.

3

### COMPOSITION/INFORMATION ON INGREDIENTS

**Ingredients:**

Cas #	Chemical Name	Perc.	OSHA PEL (ppm)	ACGIH TLV(ppm)	Carcin. Ref.
1310-73-2	Sodium hydroxide (Caustic Soda)	5-15%	2 mg/M3	2 mg/M3	D
111-76-2	Ethylene glycol monobutyl ether	5-15%	25	25	D
NA	surfactant blend	5-25%	NA	NA	D

## Wheel Luster

MSDS Number: V69E

Revision Date: 6/9/2015

Page 3 of 6

### 4 FIRST AID MEASURES

- Inhalation:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical advice/attention.
- Skin Contact:** In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Get immediate medical advice/attention.
- Eye Contact:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get immediate medical advice/attention.
- Ingestion:** If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.

### 5 FIRE FIGHTING MEASURES

- Flammability:** Not determined
- Flash Point:** None to boiling
- Flash Point Method:** Not available

Extinguishing media: Foam, dry chemical, carbon dioxide, water

Special fire fighting procedures: Full fire fighting turn out gear and respiratory protection (SCBA).

Unusual Fire &amp; Explosion Hazards: None

### 6 ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Avoid any contact with the skin and eyes.

Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Scoop up material and place in a disposal container. Provide ventilation.

### 7 HANDLING AND STORAGE

**Handling Precautions:** Corrosive liquid. Do not breathe gas/fumes/vapor/spray. Use only in well-ventilated areas. Do not get in eyes, on skin, or on clothing. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Handle in accordance with good industrial hygiene and safety practices.

**Storage Requirements:** Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking. Corrosive liquid. Handle all containers carefully. Keep out of reach of children.

Keep container tightly closed and in a well-ventilated place. Store locked up.

## Wheel Luster

MSDS Number: V69E

Revision Date: 6/9/2015

Page 4 of 6

**8**

### EXPOSURE CONTROLS/PERSONAL PROTECTION

**Engineering Controls:** Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

**Personal Protective Equip:** HMIS PP, B | Goggles, Gloves  
 Respiratory Protection: None required under normal use conditions.  
 Protective gloves: Chemical resistant, rubber, PVC  
 Eye protection: Safety glasses/goggles

In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking.

**9**

### PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance:</b>	Clear, yellow	<b>Odor:</b>	Characteristic
<b>Physical State:</b>	Liquid	<b>Solubility:</b>	Complete
<b>Spec Grav./Density:</b>	(H2O=1): 1.08 +/- 0.05	<b>Vapor Density:</b>	(Air=1): Not available
<b>Vapor Pressure:</b>	ND	<b>VOC:</b>	Not available
<b>pH:</b>	>13		

**10**

### STABILITY AND REACTIVITY

**Stability:** Stable.

**Conditions to Avoid:** NA

**Materials to Avoid:** Oxidizing agents and strong acids.

**Hazardous Decomposition:** Carbon dioxide, carbon monoxide

**Hazardous Polymerization:** Will not occur

**11**

### TOXICOLOGICAL INFORMATION

Data summary for the components are as follows:

Sodium hydroxide (1310-73-2)  
 Dermal LD50 1350 mg/kg (Rabbit)

## Wheel Luster

MSDS Number: V69E

Revision Date: 6/9/2015

Page 5 of 6

12

### ECOLOGICAL INFORMATION

#### Aquatic Toxicity

Data summary for the components are as follows:

Sodium hydroxide	(1310-73-2)	
Freshwater Fish	LC50	25ppm, 24hr, brook trout
	LC50	48ppm king salmon
Invertebrate	EC50	100 ppm daphnia magna
	EC50	33-100 ppm, 48hr, shrimp
	EC50	330-1000 ppm, 48hr, cockle

This material is not expected to bioconcentrate in organisms.

13

### DISPOSAL CONSIDERATIONS

This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

14

### TRANSPORT INFORMATION

Proper Shipping Name: NA 1760, Compounds, Cleaning Liquid, (Sodium Hydroxide), 8, PG II

15

### REGULATORY INFORMATION

COMPONENT / (CAS/PERC) / CODES

-----  
\*Sodium hydroxide (Caustic Soda) (1310732 5-15%) CERCLA, CSWHS, MASS, OSHAWAC, PA, TSCA, TXAIR

\*Ethylene glycol monobutyl ether (111762 5-15%) HAP, MASS, OSHAWAC, PA, SARA313, TSCA, TXAIR

#### REGULATORY KEY DESCRIPTIONS

-----  
CERCLA = Superfund clean up substance  
CSWHS = Clean water Act Hazardous substances  
MASS = MA Massachusetts Hazardous Substances List  
OSHAWAC = OSHA workplace Air Contaminants  
PA = PA Right-To-Know List of Hazardous Substances  
TXAIR = TX Air Contaminants with Health Effects Screening Level  
TSCA = Toxic Substances Control Act  
HAP = Hazardous Air Pollutants  
SARA313 = SARA 313 Title III Toxic Chemicals

---

**Wheel Luster**

MSDS Number: V69E

Revision Date: 6/9/2015

Page 6 of 6

16

**OTHER INFORMATION**

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. \*\* Chemical listed as carcinogen or potential carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not listed [e] Animal Data only  
N/A = Not available N/D = Not determined