

6000004235-001_TERAND-77912 11/17 STD - USG

A unique one part urethane foam which expands as it dries and solidifies. Fills cracks and holes that caulk can't! Sprays as a liquid then expands and cures to a durable semi-rigid closed cell foam insulation. Each can dispenses over 800 linear feet of product when sprayed in a 3/8 inch cured bead (based on theoretical yield). Forms a water resistant, weather resistant and airtight bond on masonry, wood, metal, glass, tile and most plastics. Dries tack free in 10 minutes. Cures completely in 8 to 24 hours, depending on humidity. Fills cracks and plugs holes eliminating energy escape of the entrance of insects or rodents. Seals out Radon Gas. Deadens Sound when applied to sheet metal. Easy to use. Conforms to any shape as it expands.

USE FOR: An insulating sealant on and around Air Conditioning, Ventilation and Heating Ducts, Plumbing, Window A/C Units, Spas, Hot Tubs, Boats, RV's, Electrical Equipment, Appliances, Refrigeration Units, Carpentry, Masonry, Conversion Vans and Buses, Auto and Truck Doors.

READ ENTIRE CAUTION PARAGRAPH PRIOR TO USING

Use only when container is between 65°F and 85°F. Can must be at room temperature for several hours prior to use. **PERSONAL PROTECTION:** Wear gloves and protective eyewear during use. Use only in well ventilated areas. **SURFACE PREPARATION:** Protect surrounding area with drop cloth or newspaper. Clean surface to remove loose dirt, debris, oil or grease. Mask adjacent areas with tape, paper or poly film.

DIRECTIONS: This product is extremely flammable. Shake can vigorously for one minute prior to use. Screw trigger / tube assembly onto valve stem, being careful not to actuate valve. Foam expands 2 to 3 times in size. Test in an experimental area prior to actual use. INVERT CAN and press trigger slowly. Do not fill cavity completely full! Fill cavity only 40% as product will expand 200 -300%. Release trigger 5 seconds before desired end point, but keep moving as foam will continue to be released. Clean up unwanted uncured foam immediately with paint thinner or acetone. Cured foam can be trimmed with a sharp knife or by sanding. Exposed foam should be covered with paint or stain. **TO STORE:** Leave trigger and tube on can and store in upright position. **TO REUSE:** Cut off one inch of extension tube and follow directions. Remainder of can must be used within 30 days.

EXPANDABLE INSULATING FOAM SEALANT

DANGER: Extremely flammable aerosol. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. In case of inadequate ventilation wear respiratory protection. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 49°C/120°F. Dispose of contents/ container in accordance with local/regional/national/international regulations.

FIRST AID: IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. **IF INHALED:** If breathing is difficult, remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a poison center/doctor. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. **IF EXPOSED OR CONCERNED:** Get medical advice/attention. **IF SWALLOWED:** Rinse mouth. Get medical attention if symptoms occur.

CONTAINS (CAS No.): Butane (106-97-8), Dimethyl Ether (115-10-5), Methylene bisphenol isocyanate (101-68-8), Propane (74-98-4) and Diphenylmethane Diisocyanate [isomers and Homologues] (9016-67-9).

Manufactured By:

TERAND
INDUSTRIES, INC.
1000 Integram Drive
Pacific, MO 63069
800-327-1835
www.cpaeroscience.com



CAUTION: Use with adequate ventilation. Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Lung, skin, and eye irritant. Always provide sufficient cross-ventilation to prevent build-up of vapors during dispensing and cure. Avoid contact with skin and eyes. Avoid prolonged or repeated breathing of vapor.

CONTACT: Use a rag to remove excess foam from skin and remove contaminated clothing. Use of a mild solvent, such as acetone (nail polish remover) or mineral spirits, may help in removing uncured residue foam from clothing or other surfaces. (Avoid eye contact) Cured foam may be removed by persistent washing with soap and water. If irritation develops, use mild skin cream. If irritation persists seek medical attention.

KEEP OUT OF REACH OF CHILDREN

See Safety Data Sheet for complete safety information.

24 HOUR MEDICAL EMERGENCY: 1-866-636-8855



PLEASE RECYCLE
WHEN EMPTY



MADE IN THE
U.S.A.



EXPANDABLE INSULATING FOAM SEALANT

77912



- Cuts Energy Costs
- Contains Flame Retardant
- Fills Holes, Seals Out Pests,
Stops Dirt and Drafts, and
Dampens Sound
- 1" Thickness Yields R-5
Insulating Factor

DANGER: EXTREMELY FLAMMABLE.
CONTENTS UNDER PRESSURE.
IRRITANT. SEE OTHER CAUTIONS ON
BACK PANEL.

NET WT. 12 OZ / 340 g